



ŞİŞECAM MULTI END ROVING

MULTI END ROVING FOR SPRAY-UP

KCR2(E)

KCR2(E) multi end roving is made from E-Glass

Features and Benefits

- Good unwinding
- Good choppability and uniform dispersion of fibers
- No static load
- Fast wet-out and wet through
- Low resin consumption
- Very low fuzz during processing
- Easy to apply on vertical surfaces

Designed for spray-up applications



PRODUCT SPECIFICATION

Glass Type	E	Moisture Content (%)	max. 0,1
Roving Tex (g/1000m)	2400 ± %5	Sizing Content (%)	0,90 ± 0,15
Filament Diameter (μ)	Nom. 13	Sizing Type	Silane
Split Tex (g/1000m)	Nom. 60	Resin Compatibility	Polyester, Vinyl ester

BOBBIN DIMENSIONS AND PACKAGING

Inner Diameter (mm)	External Diameter (mm)	Weight (kg)	Height (mm)
100	300	Nom. 23	260

Packaging	Number of bobbins per pallet	Number of layers per pallet	Pallet Dimensions (cm)	Pallet Height (cm)	Pallet Net Weight (kg)	Number of ends	Number of bobbins per layer
Bulk Packaging	48	4	96 x 128 (E)	125	1100	0-1-2-3-4	12

Product should be stored in dry area at room temperature and relative humidity of approx 65%

Product should be conditioned for 24 hours in the work area prior to use.
In case of partial usage, package should be re-sealed.

ŞİŞECAM ELYAF SANAYİİ A.Ş.

İçmeler Mahallesi, D-100 Karayolu Caddesi,
No: 44B 34947 Tuzla İstanbul Turkey

T +90 850 206 15 92
T +90 850 206 15 96

www.sisecamchemicals.com