



SİŞECAM MULTI END ROVING

MULTI END ROVING FOR CHOPPING ROVING APPLICATIONS

KCR5(M):

KCR5(M) multi end roving is from E-Glass with,

- Good unwinding,
- Good choppability and uniform dispersion,
- None of static electricity,
- Fast reaction with polyester resin and good wetting-out,
- No fuzz properties,

for general purpose chopping applications. The silane based sizing is compatible with polyester resins.



Code for ordering	:	KCR5(M)-2400 (+Packaging Code)
Identification	:	KCR5(M)-2400 (05)-13-(40) (+Packaging Code)

Product Name	:	KCR5(M)	CE Sizing Code	:	05
Roving Tex Count	:	2400	Filament Diameter	:	13
			Split Tex	:	40

PRODUCT SPECIFICATION:

Glass Type	E	Moisture Content (%)	max. 0,1
Roving Tex (g/1000m)	2400 ± %5	Sizing Content (%)	0,80 ± 0,30
Filament Diameter (μ)	Nom. 13	Sizing Type	Silane
Split Tex (g/1000m)	Nom. 40	Resin Compatibility	Polyester
		Wet-out	Fast

BOBBIN MEASUREMENTS AND PACKAGING:

Inner Diameter (mm)	External Diameter (mm)	Weight (kg)	Height (mm)
100	300	Nom. 23	260

Packaging	Number of bobbins per pallet	Number of layers per pallet	Pallet Dimension (cm)	Pallet Height (cm)	Pallet Net Weight (kg)	Number of ends	Number of bobbins per layer
Bulk Packaging (Z)	48	4	96 x 128 (E)	125	1100	0-1-2-3-4	12



KCR5(M) multi end rovings are produced conforming ISO 9001 : 2008.

Product characteristics may vary depending on developments. The information given herein supplied only for the guidance of our customers and implies no responsibility of our part.